

HSF

TECHNICAL SPECS:

Current Rating:1.0AMP

Contact Resistance:10mΩ Max

Dielectric Strength: Min 500VRMS

Mechanical Life: Min 500 cycles

Mating Pin:Ø0.38 to Ø0.50mm

Forces: (polished steel gauge Ø0.41mm)

Insertion:150g Max/Pin, Withdrawal:30g Min/Pin



Operation Temperature:-40°C to +105°C

Sleeve:Brass CuZn36Pb3(C36000),Sn over Ni

Contact Clip(6 finger):BeCu(C17200),Au or Sn over Ni

Insulator Material:PPS+30%G.F(UL94V-0)

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)





Ordering Information

3524-382 XX S XX 060 X 1

No. of Pin
2~50PIN

Contact Plating
S0=Gold Flash/Tin
S3=10u"Gold/Tin
S4=15u"Gold/Tin
S5=30u"Gold/Tin
SN=Tin

Packing
A=Tray
T=Tube



Item	Pitch	Mating
Standard	1.27	3514
Alternate		

Item	Pitch	Mating
Standard	1.27	3514
Alternate		

OPERATION	DRAW	DATE	SCALE	FIT	PART NO.
X.X ±0.40	JYHuang	2012/10/16	UNIT	mm	3524-382XXSXX060X1
X.XX ±0.25	CHECK	DATE	SIZE	A4	TITLE:
X.XXX ±0.15			SHEET	1/1	1.27mm MACHINED FEMALE HEADER
Angle ± 3°	APPROVE	DATE	PROJ.		DUAL ROW 180° Pin Length 6.0mm
DIM TOL					Customer NO.

WCON

Http: www.wcon.com

WCON-Dongguan
Tel: +86 769 85358920
Fax: +86 769 85358915
E-mail: sales@wcon.com

WCON-Kunshan
Tel: +86 512 57468408
Fax: +86 512 57468468
E-mail: salesks@wcon.com