


Recommended P.C.B Layout(Top Side)


(PCB BOARD TOLERANCE $\pm$ 0.05)

Rated Voltage: 250V AC/DC
 Rated Current: 2.0AMP
 Contact Resistance: 20m Ω Max
 Withstand Voltage: 800V AC/minute
 Insulation Resistance: 1000M Ω Min
 Operation Temperature: -40 $^{\circ}$ C to +105 $^{\circ}$ C

Contact plating: Au or Sn over Ni
Insulator Material: PA46+30%G.F. Or
PA66+25%G.F.(UL94V-0)



WF2002 - WS_H_XX_X_X_X



Circuit	Part No.	Dimension			
		A	B	C	D
04	WF2002-WS04XXXX	2.00	4.80	6.00	---
06	WF2002-WS06XXXX	4.00	6.80	8.00	2.00
08	WF2002-WS08XXXX	6.00	8.80	10.00	4.00
10	WF2002-WS10XXXX	8.00	10.80	12.00	6.00
12	WF2002-WS12XXXX	10.00	12.80	14.00	8.00
14	WF2002-WS14XXXX	12.00	14.80	16.00	10.00
16	WF2002-WS16XXXX	14.00	16.80	18.00	12.00
18	WF2002-WS18XXXX	16.00	18.80	20.00	14.00
20	WF2002-WS20XXXX	18.00	20.80	22.00	16.00
22	WF2002-WS22XXXX	20.00	22.80	24.00	18.00
24	WF2002-WS24XXXX	22.00	24.80	26.00	20.00
26	WF2002-WS26XXXX	24.00	26.80	28.00	22.00
28	WF2002-WS28XXXX	26.00	28.80	30.00	24.00
30	WF2002-WS30XXXX	28.00	30.80	32.00	26.00
32	WF2002-WS32XXXX	30.00	32.80	34.00	28.00
34	WF2002-WS34XXXX	32.00	34.80	36.00	30.00
36	WF2002-WS36XXXX	34.00	36.80	38.00	32.00
38	WF2002-WS38XXXX	36.00	38.80	40.00	34.00
40	WF2002-WS40XXXX	38.00	40.80	42.00	36.00
42	WF2002-WS42XXXX	40.00	42.80	44.00	38.00
44	WF2002-WS44XXXX	42.00	44.80	46.00	40.00
46	WF2002-WS46XXXX	44.00	46.80	48.00	42.00
48	WF2002-WS48XXXX	46.00	48.80	50.00	44.00
50	WF2002-WS50XXXX	48.00	50.80	52.00	46.00

